



The Steel Company of Canada

Basic Blast Furnace Slag
Safety Data Sheet (SDS)

Section 1 – Identification

1(a) Product Identifier Used on Label: Basic Blast Furnace Slag

1(b) Other Means of Identification: Blast Furnace Slag, Air Cooled Blast Furnace Slag

1(c) Recommended Use of the Chemical and Restrictions on Use: None

1(d) Name, Address, and Telephone Number:

Stelco Inc.

386 Wilcox Street

Hamilton, ON L8L 8K5


Phone number : (905) 528-2511 (8:00 am to 5:00 pm)

1(e) Emergency Phone Number: 1-888-CAN-UTEC (226-8832) or 613-996-6666

Section 2 – Hazard(s) Identification

2(a) Classification of the Chemical: Basic Blast Furnace Slag is considered a hazardous material according to the criteria specified in REACH [REGULATION (EC) No 1907/2006], CLP [REGULATION (EC) No 1272/2008], OSHA 29 CFR 1910.1200 Hazard Communication Standard and the Canadian Hazardous Products Regulations. The categories of Health Hazards as defined in “GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)”, have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal Word, Hazard Statement(s), Symbols and Precautionary Statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)	Precautionary Statement(s)
	Carcinogenicity - 1A Single Target Organ Toxicity (STOT) Single Exposure - 2 STOT Repeated Exposure - 1	Danger	May cause cancer. May cause mechanical irritation to skin and lung irritation. Causes damage to lungs through prolonged or repeated exposure.	Do not breathe dusts or fumes. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. If exposed, concerned or feel unwell: Get medical advice/attention, call a poison center or doctor/physician. Store locked up. Dispose of contents in accordance with federal, provincial, state and local regulations.

2(c) Hazards Not Otherwise Classified: None Known

2(d) Unknown Acute Toxicity Statement (mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical Name, Common Name (Synonyms), CAS Number and Other Identifiers, and Concentration:

Chemical Name	CAS Number	EC Number	% weight
Slags, ferrous metal, blast furnace	65996-69-2	266-002-0	100%
The following components comprise this Basic Blast Furnace Slag product and were used for hazard determination:			
Metallic Silicates and Aluminosilicates *	Various	Various	94-100
Crystalline Silica (as Quartz)	14808-60-7	238-878-4	0-2.5
Calcium Sulfide	20548-54-3	234-873-5	2-4

EC- European Community

CAS- Chemical Abstract Service

*The majority of components in slag are composed of various metallic silicates (Iron, Calcium, Magnesium, Aluminum, and Titanium Silicates), including: Dicalcium Silicate (Ca₂SiO₄) 14284-23-2, Merwinite (Ca₃MgSi₂O₈) 13813-64-4, and Gehlenite (Ca₂Al₂SiO₇) 1302-56-3

Section 4 – First-aid Measures

4(a) Description of Necessary Measures: If exposed, concerned or feel unwell: Get medical advice/attention, call a poison center or doctor/physician.

- **Inhalation:** If exposed, concerned or feel unwell: Get medical advice/attention, call a poison center or doctor/physician.
- **Eye Contact:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **Skin Contact:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- **Ingestion:** If swallowed: Rinse mouth.

4(b) Most Important Symptoms/Effects, Acute and Delayed (Chronic):

Acute effects:

- **Inhalation:** Excessive exposure to high concentrations of dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract.
- **Eye:** Excessive exposure to high concentrations of dust may cause irritation to the eyes.
- **Skin:** Skin contact with dusts may cause irritation or dermatitis.
- **Ingestion:** Ingestion of dust may cause nausea and/or vomiting.

Chronic Effects:

Individuals with chronic respiratory disorders (i.e., asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any airborne particulate matter exposure. Persons with pre-existing skin disorders may be more susceptible to dermatitis.

4(c) Immediate Medical Attention and Special Treatment: Treat symptomatically.

Section 5 – Fire-fighting Measures

5(a) Suitable (and unsuitable) Extinguishing Media: Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards Arising from the Chemical: Not applicable for solid product.

5(c) Special Protective Equipment and Precautions for Fire-fighters: Self-contained NIOSH-approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods into sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Personnel should be protected against contact with eyes and skin. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways.

6(b) Methods and Materials for Containment and Clean Up: Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, provincial, state, and local regulations. Follow applicable regulations (e.g. 29 CFR 1910.120) and all other pertinent federal, provincial, state, and local requirements.

Section 7 - Handling and Storage

7(a) Precautions for Safe Handling: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not breathe dusts. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Emergency safety showers and eye wash stations should be present.

7(b) Conditions for Safe Storage, Including any Incompatibilities: Whenever feasible, store locked up.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): The following exposure limits are offered as reference, for an experienced industrial hygienist to review.

Ingredients	Ontario TWA ¹	ACGIH TLV ²	OSHA PEL ³	NIOSH REL ⁴	IDLH ⁵
Metallic Silicates	10 mg/m ³ (as inhalable fraction ⁶ , PNOS ⁷) 3.0 mg/m ³ (as respirable fraction ⁸ , PNOS ⁷)	10 mg/m ³ (as inhalable fraction ⁶ , PNOS) 3.0 mg/m ³ (as respirable fraction ⁸ , PNOS)	15 mg/m ³ (as total dust, PNOR ⁹) 5.0 mg/m ³ (as respirable fraction, PNOR ⁹)	NE	NE
Crystalline Silica (as Quartz)	0.10 mg/m ³ (respirable fraction ⁸)	0.025 mg/m ³ (respirable fraction ⁸ , all forms)	0.05 mg/m ³ (respirable fraction ⁸ , all forms) 0.025 mg/m ³ AL (respirable fraction ⁸ , all forms)	0.05 mg/m ³	50 mg/m ³

Calcium Sulfide	NE	NE	NE	NE	NE
-----------------	----	----	----	----	----

Section 8 - Exposure Controls / Personal Protection (continued)

8(a) Occupational Exposure Limits (OELs)(continued):

1. Time-Weighted Average (TWA) limits established by the Ontario Ministry of Labour are 8-hour TWA concentrations unless otherwise noted.
2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
3. OSHA PELs (Permissible Exposure Limits) are 8-hour TWA (Time-Weighted Average) concentrations unless otherwise noted. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
4. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the U.S. federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
5. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994.
6. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices – as cited by Ministry of Labour (MOL) R.R.O. 833/90.
7. P.NOS. Particles (Insoluble or Poorly Soluble) Not Otherwise Specified defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices – as cited by Ministry of Labour (MOL) R.R.O. 833/90.
8. Respirable fraction. The concentration of respirable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices– as cited by Ministry of Labour (MOL) R.R.O. 833/90.
9. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by a limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction.

8(b) Appropriate Engineering Controls: Local exhaust ventilation should be used to control the emission of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations. Emergency eye wash stations and deluge safety showers should be available in the work area.

8(c) Individual Protection Measures:

- **Respiratory Protection:** Seek professional advice prior to respirator selection and use. In the US, follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. In Ontario, follow CSA Standard Z94.4-11 "Selection Care and Use of Respirators" or the "NIOSH Guide to the Selection and Use of Particulate Respirators (1996)" for additional information. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

- **Eyes:** Wear eye protection/face protection. A face shield should be used when appropriate to prevent contact with splashed materials. Chemical goggles, face shields or glasses should be worn to prevent eye contact. Contact lenses should not be worn where industrial exposure to this material is likely.
- **Skin:** Persons handling this product should wear appropriate clothing to prevent skin contact. Wear protective gloves.
- **Other Protective Equipment:** An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties




- | | |
|--|--|
| 9(a) Appearance (physical state, color, etc.): Light to dark, vesicular, stone-like | 9(j) Upper/lower Flammability or Explosive Limits: NA |
| 9(b) Odor: slight sulfur odor | 9(k) Vapor Pressure: NA |
| 9(c) Odor Threshold: NA | 9(l) Vapor Density (Air = 1): NA |
| 9(d) pH: NA | 9(m) Relative Density: NA |
| 9(e) Melting Point/Freezing Point: 1480°C (~ 2700°F) | 9(n) Solubility(ies): Insoluble |
| 9(f) Initial Boiling Point and Boiling Range: N/A | 9(o) Partition Coefficient n-octanol/water: NA |
| 9(g) Flash Point: NA | 9(p) Auto-ignition Temperature: ND |
| 9(h) Evaporation Rate: NA | 9(q) Decomposition Temperature: ND |
| 9(i) Flammability (solid, gas): Not flammable | 9(r) Viscosity: ND |
- NA - Not Applicable
ND - Not Determined for product as a whole

Section 10 - Stability and Reactivity

- 10(a) Reactivity:** Not Determined (ND)
- 10(b) Chemical Stability:** Basic Blast Furnace Slag is stable under normal storage and handling conditions.
- 10(c) Possibility of Hazardous Reaction:** None Known
- 10(d) Conditions to Avoid:** Storage with incompatible materials. Flames and ignition sources where dust can accumulate.
- 10(e) Incompatible Materials:** Strong acids and bases.
- 10(f) Hazardous Decomposition Products:** Oxides of carbon, sulfur, metal oxides, hydrogen sulfide and other toxic vapors may be released at elevated temperatures.

Section 11 - Toxicological Information

11(a-j) Information on Toxicological Effects: The following toxicity data has been determined for Basic Blast Furnace Slag by using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of WHMIS, OSHA and the EU CPL:

Hazard Classifications	Hazard Category		Hazard Symbols	Signal Word	Hazard Statement
	EU	OSHA / WHMIS			
Germ Cell Mutagenicity (covers Categories 1A, 1B and 2)	2	NR *	NA	NA	NA
Carcinogenicity (covers Categories 1A, 1B and 2)	NR	1A ^e		Danger	May cause cancer.
Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3)	2	2 ⁱ		Warning	May cause mechanical irritation to skin and lung irritation.
STOT Following Repeated Exposure (covers Categories 1 and 2)	1	1 ^j		Danger	Causes damage to lungs through prolonged or repeated exposure.

* NR Not Rated - Available data does not meet criteria for classification.

The Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

- a. No LC50 or LD50 has been established for **Basic Blast Furnace Slag**. The following data has been determined for the components:
 - **Silica:** Rat LD50 = 500 mg/kg (Oral/ Rat)
- b. No Skin (Dermal) Irritation data available for Galvanized (Hot Dipped) Sheet – High Strength Steel as a mixture. The following Skin (Dermal) Irritation information was found for the components:
 - **Merwinite:** Causes mild skin irritation.
 - **Calcium Sulfide:** Causes Skin irritation.
- c. No Eye Irritation data available for **Basic Blast Furnace Slag** as a mixture. The following Eye Irritation information was found for the components:
 - **Merwinite:** Causes eye irritation.
 - **Crystalline Silica:** May cause abrasion of the cornea.
 - **Calcium Sulfide:** Causes eye irritation.
- d. No Skin (Dermal)/Respiratory Sensitization data available for **Basic Blast Furnace Slag** as a mixture or its individual components.
- e. No Aspiration Hazard data available for **Basic Blast Furnace Slag** as a mixture or its individual components.
- f. No Germ Cell Mutagenicity data available for **Basic Blast Furnace Slag** as a mixture or its individual components.
- g. Carcinogenicity: IARC, NTP, and OSHA do not list **Basic Blast Furnace Slag** as carcinogens. The following Carcinogenicity information was found for the components:
 - **Silicon Dioxide:** Repeated exposure to crystalline silica causes lung cancer in exposed humans. IARC-1, NTP-1, TLV-A2, and OSHA.
- h. No Toxic Reproduction data available for **Basic Blast Furnace Slag** as a mixture or its individual components.
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Basic Blast Furnace Slag** as a mixture. The following STOT following a Single Exposure data was found for the components:
 - **Silicon Dioxide:** Single exposure to very high airborne levels may cause lung irritation in exposed humans.
 - **Calcium Sulfide:** May cause respiratory irritation. Contact with stomach acids may liberate H₂S.

Section 11 - Toxicological Information (continued)

11(a-j) Information on Toxicological Effects (continued):

j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Basic Blast Furnace Slag** as a whole. The following STOT following Repeated Exposure data was found for the components:

- **Silicon Dioxide:** Repeated exposure to crystalline silica causes silicosis and kidney damage as well as increased incidence of autoimmune disorders in humans.

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2017, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s):

Acute Effects by component:

- **Metallic Silicates:** Magnesium Silicate may irritate the eyes. Potassium Silicate may be harmful if swallowed or contacts skin. Calcium silicate may be harmful if swallowed.
- **Crystalline Silica (Silicon Dioxide):** Causes irritation and inflammation of the respiratory tract. May cause abrasion of the cornea. Inhalation may cause cough. A single exposure to very high airborne levels may cause lung irritation in exposed humans.
- **Calcium Sulfide:** Causes skin irritation, eye irritation and may cause respiratory irritation.

Delayed (chronic) Effects by Component:

- **Metallic Silicates:** Magnesium and Potassium Silicates are suspected of causing cancer by inhalation. Lifetime inhalation exposure of rats and mice to atmospheres of magnesium silicate resulted in interstitial fibrosis of the lung and reduced pulmonary function in rats at ≥ 6 mg/m³. Calcium Silicate exposure to wollastonite miners suggests that occupational exposure can cause impaired respiratory function and pneumoconiosis.
- **Crystalline Silica (Silicon Dioxide):** Inhalation of quartz is classified by IARC as a human carcinogen. Chronic exposure can cause silicosis, a form of lung scarring that can cause shortness of breath, reduced lung function, and in severe cases, death. Repeated exposure may cause kidney damage as well as increased incidence of autoimmune disorder.
- **Calcium Sulfide:** Not Reported/Not Classified

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No data available for the product, **Basic Blast Furnace Slag** as a whole. However, individual components of the product have been found to be toxic to the environment. The following may migrate into soil and groundwater and be ingested by wildlife.

- **Calcium Sulfide:** EU RAR lists as Category 1 Very toxic to aquatic life with long lasting effects.

12(b) Persistence & Degradability: No Data Available

12(c) Bioaccumulative Potential: No Data Available

12(d) Mobility (in soil): No Data Available

12(e) Other Adverse Effects: None Known

Additional Information:

Hazard Category: Category 1 Chronic to the Aquatic Environment (Calcium Sulfide)

Signal Word: Warning

Hazard Symbol:



Hazard Statement: Very Toxic to aquatic life with long lasting effects.

Section 13 - Disposal Considerations

Disposal: Dispose of contents/container in accordance with local/regional/international regulations.

Container Cleaning and Disposal: Follow applicable federal, provincial, state and local regulations. Observe safe handling precautions. European Waste Catalogue 10-02-99 (unprocessed slag), or 10-02-99 (wastes not otherwise specified).

Please note this information is for Basic Blast Furnace Slag in its original form. Any alterations can void this information.

Basic Blast Furnace Slag

Rev. 6/17

Section 14 - Transport Information

14 (a-g) Transportation Information:

TDG/US Department of Transportation (DOT) under federal TDG and 49 CFR 172.101 does not regulate **Basic Blast Furnace Slag** as a hazardous material. All federal, provincial, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: NA Shipping Symbols: NA Hazard Class: NA UN No.: NA Packing Group: NA DOT/ IMO Label: NA Special Provisions (172.102): NA	Packaging Authorizations a) Exceptions: NA b) Non-bulk: NA c) Bulk: NA	Quantity Limitations a) Passenger, Aircraft, or Railcar: NA b) Cargo Aircraft Only: NA Vessel Stowage Requirements a) Vessel Stowage: NA b) Other: NA DOT Reportable Quantities: NA
---	---	--

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate **Basic Blast Furnace Slag** as a hazardous material.

Shipping Name: NA Classification Code: NA UN No.: NA Packing Group: NA ADR Label: NA Special Provisions: NA Limited Quantities: NA	Packaging a) Packing Instructions: NA b) Special Packing Provisions: NA c) Mixed Packing Provisions: NA	Portable Tanks & Bulk Containers a) Instructions: NA b) Special Provisions: NA
---	--	---

International Air Transport Association (IATA) does not regulate **Basic Blast Furnace Slag** as a hazardous material.

Shipping Name: NA Class/Division: NA Hazard Label (s): NA UN No.: NA Packing Group: NA Excepted Quantities (EQ): NA	Passenger & Cargo Aircraft Limited Quantity (EQ) Pkg Inst: NA Pkg Inst: NA Max Net Qty/Pkg: NA Max Net Qty/Pkg: NA		Cargo Aircraft Only Pkg Inst: NA Max Net Qty/Pkg: NA	Special Provisions: NA ERG Code: NA
--	---	--	---	--

Pkg Inst – Packing Instructions Max Net Qty/Pkg – Maximum Net Quantity per Package ERG – Emergency Response Drill Code

Transport Dangerous Goods (TDG) Classification: **Basic Blast Furnace Slag** does not have a **Transport Dangerous Goods (TDG)** classification.

Section 15 - Regulatory Information

Regulatory Information: *The following listing of regulations relating to a Stelco product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.* This product and/or its constituents are subject to the following regulations:

SARA Potential Hazard Categories: Immediate Acute Health Hazard, Delayed Chronic Health Hazard.

Section 313 Supplier Notification: The product, **Basic Blast Furnace Slag** does not contain any of the toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

State Regulations: The product, **Basic Blast Furnace Slag** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

California Prop. 65: Contains elements known to the State of California to cause cancer or reproductive toxicity. This includes Crystalline silica (airborne particles of respirable size only).

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Section 16 - Other Information

Prepared By: Stelco Inc.

Revision History:

- 06/30/2017 – Update to Stelco
- 04/14/2015 - Revision
- 07/07/2014 - Update to OSHA HAZCOM 2012
- 07/25/2011 – Update of content and format to comply with GHS
- 10/25/1985 - Original


Additional Information:

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

HEALTH= 1, * Denotes possible chronic hazard if airborne dusts or fumes are generated
Irritation or minor reversible injury possible.
FIRE= 0, Materials that will not burn.
PHYSICAL HAZARDS = 0, Materials that are normally stable, even under fire conditions, will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.
FIRE = 0, Materials that will not burn.
INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not and reactive with water.

ABBREVIATIONS/ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found
BEIs	Biological Exposure Indices	NIOSH	National Institute for Occupational Safety and Health
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	ORC	Organization Resources Counselors
CFR	Code of Federal Regulations	OSHA	Occupational Safety and Health Administration
CNS	Central Nervous System	PEL	Permissible Exposure Limit
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract	PNOR	Particulate Not Otherwise Regulated
HMIS	Hazardous Materials Identification System	PNOC	Particulate Not Otherwise Classified
IARC	International Agency for Research on Cancer	PPE	Personal Protective Equipment
LC50	Median Lethal Concentration	ppm	parts per million
LD50	Median Lethal Dose	RCRA	Resource Conservation and Recovery Act
LD_{Lo}	Lowest Dose to have killed animals or humans	RTECS	Registry of Toxic Effects of Chemical Substances
LEL	Lower Explosive Limit	SARA	Superfund Amendment and Reauthorization Act
µg/m³	microgram per cubic meter of air	SCBA	Self-contained Breathing Apparatus
mg/m³	milligram per cubic meter of air	STEL	Short-term Exposure Limit
mppcf	million particles per cubic foot	TLV	Threshold Limit Value
SDS	Safety Data Sheet	TWA	Time-weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
MOL	Ontario Ministry of Labour	WHMIS	Workplace Hazardous Materials Information System
NFPA	National Fire Protection Association		

Disclaimer: This information is taken from sources or based upon data believed to be reliable. However, Stelco Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.



The Steel Company of Canada

Basic Blast Furnace Slag

Signal Word: DANGER

Symbols:



HAZARD STATEMENTS:

May cause cancer.
May cause mechanical irritation to skin and lung irritation.
Causes damage to lungs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

Do not breathe dusts or fumes.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not eat, drink or smoke when using this product.
If exposed, concerned or feel unwell: Get medical advice/attention, call a poison center or doctor/physician.
Store locked up.
Dispose of contents in accordance with federal, provincial, state and local regulations.

Stelco Inc.
386 Wilcox Street
Hamilton, ON L8L 8K5
(CANUTEC)
Original Issue Date: 10/25/1985

Phone Number : (905) 528-2511 (8:00 am to 5:00 pm)
Emergency Contact: 1-888-226-8832

Revised: 06/30/2017