

# CERTIFICATE OF COMPLIANCE

**Certificate Number** MH64069  
**Report Reference** MH64069-20200428  
**Issue Date** 2020-APRIL-28

**Issued to:** Stelco Inc  
386 Wilcox St  
HAMILTON  
ON L8L 8K5 CANADA

**This certificate confirms that representative samples of** COMPONENT - COATINGS, METALLIC  
(See Addendum Page)

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**Standard(s) for Safety:** ASTM A653/A653M, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) by the Hot-Dip Process  
ASTM A90/A90M, Standard Test Method for Weight of Coating on Iron and Steel Articles with Zinc or Zinc-Alloy Coatings

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/ul/locations/>



# CERTIFICATE OF COMPLIANCE

Certificate Number MH64069  
Report Reference MH64069-20200428  
Issue Date 2020-APRIL-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Zinc-coatings, passivated G60-U as provided on hot-dipped mill-galvanized steel (0.015 – 0.071 in. nominal thickness range) and passivated G90-U as provided on hot-dipped mill-galvanized steel (0.012 – 0.071 in. nominal thickness range).



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/ul-locations/>

