



The Steel Company of Canada

**Electrical Sheet
Safety Data Sheet (SDS)**

Section 1 – Identification

- 1(a) Product Identifier Used on Label:** Electrical Sheet
1(b) Other Means of Identification: Cold Roll Motor Lamination Sheet
1(c) Recommended Use of the Chemical and Restrictions on Use: None
1(d) Name, Address, and Telephone Number:
 Stelco Inc.
 386 Wilcox Street
 Hamilton, ON L8L 8K5
 Phone number: (905) 528-2511 (8:00 am to 5:00 pm)
1(e) Emergency Phone Number: 1-888-CAN-UTEC (226-8832) or 613-996-6666

Section 2 – Hazard(s) Identification

2(a) Classification of the Chemical: As sold, this product, **Electrical Sheet** is not hazardous according to the criteria specified in REACH [REGULATION (EC) No 1907/2006], CLP [REGULATION (EC) No 1272/2008] and the Canadian Hazardous Products Regulations. Under WHMIS 2015 and 29 CFR 1910.1200 Hazard Communication Standard, steel products are considered mixtures due to further processing which may produce dusts and or fume. The categories of Health Hazards as defined in “GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)” have been evaluated. Refer to Section 3, 8 and 11 for additional information. Precautionary Statement/Emergency Overview: This formed solid metal product poses little or no immediate health or fire hazard. When product is subjected to welding, burning, melting, sawing, brazing, grinding or other similar processes, potentially hazardous airborne particulate and fumes may be generated.

2(b) Signal Word, Hazard Statement(s), Symbols and Precautionary Statement(s):

| Hazard Symbol | Hazard Classification | Signal Word | Hazard Statement(s) | Precautionary Statement(s) |
|---------------|---|---------------|--|--|
| | Carcinogenicity - 2 Toxic to Reproduction - 2 Single Target Organ Toxicity (STOT) Repeat Exposure - 1 | Danger | Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to lungs through prolonged or repeated inhalation exposure. Harmful if swallowed. May cause an allergic skin reaction. May cause respiratory irritation. Causes eye irritation. | Do not breathe dusts / fume. Wear protective gloves / protective clothing / eye protection / face protection. Contaminated work clothing must not be allowed out of the workplace. Use only outdoors or in well ventilated areas. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed, concerned or feel unwell: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Dispose of contents in accordance with federal, provincial, state and local regulations. |
| | Acute Toxicity-Oral 4 Skin Sensitization - 1 STOT Single Exposure - 3 | | | |
| NA | Eye Irritation - 2B | | | |
| | | | | |

- 2(c) Hazards Not Otherwise Classified:** None Known
2(d) Unknown Acute Toxicity Statement (mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical Name, Common Name (Synonyms), CAS Number and Other Identifiers, and Concentration:

| Chemical Name | CAS Number | EC Number | % weight |
|---------------|------------|-----------|----------|
| Iron | 7439-89-6 | 231-096-4 | >96 |
| Aluminum | 7429-90-5 | 231-072-3 | ≤1.0 |
| Manganese | 7439-96-5 | 231-105-1 | ≤2.0 |
| Nickel | 7440-02-0 | 231-111-4 | ≤0.2 |
| Silicon | 7440-21-3 | 231-130-8 | ≤2.0 |

EC- European Community

CAS- Chemical Abstract Service

Section 4 – First-aid Measures

4(a) Description of Necessary Measures: If exposed, concerned or feel unwell: Get medical advice/attention.

- **Inhalation:** **Electrical Sheet** as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed, concerned or feel unwell: Get medical advice/attention.
- **Eye Contact:** This product as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If eye irritation persists: Get medical advice/attention. If exposed, concerned or feel unwell: Get medical advice/attention.
- **Skin Contact:** If on skin: Wash thoroughly after handling. Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse.
- **Ingestion:** This product as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If exposed, concerned or feel unwell: Get medical advice/attention.

4(b) Most Important Symptoms/Effects, Acute and Delayed (Chronic):

- **Inhalation:** This product as sold/shipped is not likely to present an acute or chronic health effect.
- **Eye:** This product as sold/shipped is not likely to present an acute or chronic health effect.
- **Skin:** This product as sold/shipped is not likely to present an acute or chronic health effect.
- **Ingestion:** This product as sold/shipped is not likely to present an acute or chronic health effect.

4(c) Immediate Medical Attention and Special Treatment: None Known

Section 5 – Fire-fighting Measures

5(a) Suitable (and unsuitable) Extinguishing Media: Not applicable for **Electrical Sheet** as sold/shipped. Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards Arising from the Chemical: Not applicable for this product as sold/shipped. When burned, toxic smoke and vapor may be emitted.

5(c) Special Protective Equipment and Precautions for Fire-fighters: Self-contained NIOSH-approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: Not applicable for **Electrical Sheet** as sold/shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin.

6(b) Methods and Materials for Containment and Clean Up: Not applicable for this product as sold/shipped. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, provincial, state, and local regulations. Follow applicable regulations (e.g. 29 CFR 1910.120) and all other pertinent federal, provincial, state, and local requirements.

Section 7 - Handling and Storage

7(a) Precautions for Safe Handling: Not applicable for **Electrical Sheet** as sold/shipped. However, further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Practice good housekeeping. Avoid breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product.

7(b) Conditions for Safe Storage, Including any Incompatibilities: Store away from acids and incompatible materials.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): Electrical Sheet as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as high temperature (burning, welding, sawing, brazing, machining and grinding) may produce fumes and/or particulates. The following exposure limits are offered as reference, for an experience industrial hygienist to review.

| Ingredients | Ontario TWA ¹ | ACGIH TLV ² | OSHA PEL ³ | NIOSH REL ⁴ | IDLH ⁵ |
|-------------|--|---|--|--|------------------------------|
| Iron | 5.0 mg/m ³ (as iron oxide, respirable fraction ⁶) | 5.0 mg/m ³ (as iron oxide, respirable fraction ⁶) | 10 mg/m ³ (as iron oxide fume) | 5.0 mg/m ³ (as iron oxide dust and fume) | 2,500 mg Fe/m ³ |
| Aluminum | 1.0 mg/m ³ (respirable fraction ⁶) | 1.0 mg/m ³ (respirable fraction ⁶) | 15 mg/m ³ (total dust, PNOR) ⁸ 5.0 mg/m ³ (as respirable fraction, PNOR) | 10 mg/m ³ (as total dust) 5.0 mg/m ³ (as respirable dust) | NE |
| Manganese | 0.2 mg/m ³ | 0.02 mg/m ³ (respirable fraction ⁶) 0.1 mg/m ³ (inhalable fraction ⁷) | “C” 5.0 mg/m ³ (Fume & Mn compounds) | 1.0 mg/m ³ (Fume & Mn compounds) STEL 3.0 mg/m ³ | 500 mg Mn/m ³ |
| Nickel | 1 mg/m ³ (as inhalable fraction Ni metal) 0.1 mg/m ³ (as inhalable fraction Ni soluble compounds) 0.2 mg/m ³ (as inhalable fraction Ni insoluble compounds) | 1.5 mg/m ³ (as inhalable fraction Ni metal) 0.2 mg/m ³ (as inhalable fraction Ni inorganic only insoluble and soluble compounds) | 1.0 mg/m ³ (as Ni metal & insoluble compounds) | 0.015 mg/m ³ (as Ni metal & insoluble and soluble compounds) | 10 mg/m ³ (as Ni) |
| Silicon | 10 mg/m ³ (Inhalable PNOS) 3 mg/m ³ (Respirable PNOS) | 10 mg/m ³ (Inhalable PNOS) ⁹ 3 mg/m ³ (Respirable PNOS) | 15 mg/m ³ (total dust, PNOR) 5.0 mg/m ³ (as respirable fraction, PNOR) | 10 mg/m ³ (as total dust) 5.0 mg/m ³ (as respirable dust) | NE |

NE - None Established

1. Time-Weighted Average (TWA) limits established by the Ontario Ministry of Labour are 8-hour TWA concentrations unless otherwise noted. A Short-Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures.
2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes. A Short-Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures.
3. OSHA PELs (Permissible Exposure Limits) are 8-hour TWA (Time-Weighted Average) concentrations unless otherwise noted. A (“C”) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
4. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the U.S. federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
5. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) - Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992).NIOSH is the U.S. federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
6. Respirable fraction. The concentration of respirable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices – as cited by Ministry of Labour (MOL) R.R.O. 833/90.
7. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices – as cited by Ministry of Labour (MOL) R.R.O. 833/90.
8. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by a limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction.
9. PNOS. Particles (Insoluble or Poorly Soluble) Not Otherwise Specified defined in the ACGIH TLVs® and BEIs® based on the Documentation of the Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices – as cited by Ministry of Labour (MOL) R.R.O. 833/90.

8(b) Appropriate Engineering Controls: Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

8(c) Individual Protection Measures:

- **Respiratory Protection:** Seek professional advice prior to respirator selection and use. In the US, follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. In Ontario, follow CSA Standard Z94.4-11 “Selection Care and Use of Respirators” or the “NIOSH Guide to the Selection and Use of Particulate Respirators (1996)” for additional information. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative- pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life or Health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive- demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

Section 8 - Exposure Controls / Personal Protection (continued)

8(c) Individual Protection Measures (continued):

- **Eyes:** Wear appropriate eye protection to prevent eye contact. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- **Skin:** Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- **Other Protective Equipment:** An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties

- | | |
|---|--|
| 9(a) Appearance (physical state, color, etc.): Metallic Gray | 9(j) Upper/lower Flammability or Explosive Limits: NA |
| 9(b) Odor: Odorless | 9(k) Vapor Pressure: NA |
| 9(c) Odor Threshold: NA | 9(l) Vapor Density (Air = 1): NA |
| 9(d) pH: NA | 9(m) Relative Density: 7.85 g/cc |
| 9(e) Melting Point/Freezing Point: ~ 2750 °F (~ 1510 °C) | 9(n) Solubility(ies): Insoluble |
| 9(f) Initial Boiling Point and Boiling Range: ND | 9(o) Partition Coefficient n-octanol/water: ND |
| 9(g) Flash Point: NA | 9(p) Auto-ignition Temperature: NA |
| 9(h) Evaporation Rate: NA | 9(q) Decomposition Temperature: ND |
| 9(i) Flammability (solid, gas): Non-flammable, non-combustible | 9(r) Viscosity: NA |





NA - Not Applicable
 ND - Not Determined for product as a whole

Section 10 - Stability and Reactivity

- 10(a) Reactivity:** Not Determined (ND)
- 10(b) Chemical Stability:** Steel products are stable under normal storage and handling conditions.
- 10(c) Possibility of Hazardous Reaction:** None Known
- 10(d) Conditions to Avoid:** Storage with strong acids or calcium hypochlorite.
- 10(e) Incompatible Materials:** Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.
- 10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.



Section 11 - Toxicological Information

11(a-j) Information on Toxicological Effects: The following toxicity data has been determined for **Electrical Sheet** as a mixture when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of WHMIS, OSHA and the EU CPL:

| Hazard Classifications | Hazard Category | | Hazard Symbols | Signal Word | Hazard Statement |
|--|-----------------|-----------------|---|----------------|--|
| | EU | OSHA / WHMIS | | | |
| Acute Toxicity Hazard (covers Categories 1-5) | NA* | 4 ^a |  | Warning | Harmful if swallowed. |
| Eye Damage/Irritation (covers Categories 1, 2A, and 2B) | NA* | 2B ^c | No Pictogram | Warning | Causes eye irritation. |
| Skin/Dermal Sensitization (covers Category 1) | NA* | 1 ^d |  | Warning | May cause an allergic skin reaction. |
| Carcinogenicity (covers Categories 1A, 1B and 2) | NA* | 2 ^g |  | Warning | Suspected of causing cancer. |
| Toxic to Reproduction (covers Categories 1A, 1B and 2) | NA* | 2 ^h |  | Warning | Suspected of damaging fertility or the unborn child. |

Section 11 - Toxicological Information (continued)

11(a-j) Information on Toxicological Effects (continued):

| Hazard Classifications | Hazard Category | | Hazard Symbols | Signal Word | Hazard Statement |
|---|-----------------|----------------|---|-------------|---|
| | EU | OSHA / WHMIS | | | |
| Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3) | NA* | 3 ⁱ |  | Warning | Harmful if swallowed. |
| STOT following Repeated Exposure (covers Categories 1 and 2) | NA* | 1 ⁱ |  | Danger | Causes damage to lungs through prolonged or repeated inhalation exposure. |

* Not Applicable

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

a. No LC50 or LD50 has been established for **Electrical Sheet**. The following data has been determined for the components:

- **Iron:** Rat LD₅₀ =98.6 g/kg (REACH)
Rat LD₅₀ =1060 mg/kg (IUCLID)
LD₅₀ =984 mg/kg (IUCLID)
Rabbit LD₅₀ =890 mg/kg (IUCLID)
Guinea Pig LD₅₀ =20 g/kg (TOXNET)
Human LD_{Lo} =77 g/kg (IUCLID)
- **Aluminum:** Rat LD₅₀ > 15.9 g/kg (REACH)
- **Nickel:** LD₅₀ >9000 mg/kg (Oral/Rat); NOAEC >10.2 mg/l(Inhalation/Rat) Rat
- **Silicon:** LD₅₀ = 3160 mg/kg (Oral/Rat)
- **Manganese:** Rat LD₅₀ > 2000 mg/kg (REACH)
Rat LD₅₀ > 9000 mg/kg (NLM Toxnet)

b. No Skin (Dermal) Irritation data available for **Electrical Sheet** as a mixture or its components.

c. No Eye Irritation data available for **Electrical Sheet** as a mixture. The following Eye Irritation information was found for the components:

- **Iron and Molybdenum:** Causes eye irritation.
- **Silicon:** Slight eye irritation in rabbit protocol.
- **Nickel:** Slight eye irritation from particulate abrasion only.

d. No Skin (Dermal) Sensitization data available for **Electrical Sheet** as a mixture. The following Skin (Dermal) Sensitization information was found for the components:

- **Nickel:** May cause allergic skin sensitization.

e. No Respiratory Sensitization data available for **Electrical Sheet** as a mixture or its components.

f. No Germ Cell Mutagenicity data available for **Electrical Sheet** as a mixture. The following Mutagenicity and Genotoxicity information was found for the components:

- **Iron:** IUCLID has found some positive and negative findings *in vitro*.
- **Aluminum:** IUCLID; ATSDR have found this ingredient is not mutagenic *in vitro*; but has marginal effects *in vivo*.
- **Nickel:** EU RAR has found positive results *in vitro* and *in vivo* but insufficient data for classification.

g. Carcinogenicity: IARC, NTP, and OSHA do not list **Electrical Sheet** as carcinogens. The following Carcinogenicity information was found for the components:

- **Welding Fumes** - IARC Group 1 carcinogen, carcinogenic to humans.
- **Nickel and certain nickel compounds** – Group 2B - metallic nickel. Group 1 - nickel compounds ACGIH confirmed human carcinogen. Nickel – EURAR Insufficient evidence to conclude carcinogenic potential in animals or humans; suspect carcinogen classification Category 2 Suspected of causing cancer.

h. No Toxic to Reproduction data available for **Electrical Sheet** as a mixture. The following Toxic to Reproductive information was found for the components:

- **Nickel:** Effects on fertility.

i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Electrical Sheet** as a mixture. The following STOT following a Single Exposure data was found for the components:

- **Iron:** Irritating to respiratory tract.
- **Aluminum:** Repeated exposure associated with Asthma, fibrosis in lungs and encephalopathy in humans.

j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Electrical Sheet** as a whole. The following STOT following Repeated Exposure data was found for the components:

- **Aluminum:** Reviews have found chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.
- **Nickel:** Rat 4 wk inhalation LOEL 4 mg/m³ Lung and Lymph node histopathology. Rat 2 yr inhalation LOEL 0.1 mg/ m³ Pigment in kidney, effects on hematopoiesis spleen and bone marrow and adrenal tumor. Rat 13 Week Inhalation LOAEC 1.0 mg/m³ Lung weights, and Alveolar histopathology.
- **Manganese:** Inhalation of metal fumes - Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock *et al.*, 1966).

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs) with Other Worldwide Occupational Exposure Values 2017, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

Section 11 - Toxicological Information (continued)

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

Acute Effects by component:

- **Iron and Oxides:** Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage.
- **Aluminum:** Not Reported/ Not Classified
- **Manganese and Oxides:** Manganese and Manganese oxide are harmful if swallowed.
- **Nickel and Oxides:** Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- **Silicon and Oxides:** May be harmful if swallowed.

Delayed (chronic) Effects by Component:

- **Iron and Oxides:** Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by the International Agency for Research on Cancer (IARC).
- **Aluminum:** Chronic inhalation of finely divided powder has been reported to cause pulmonary fibrosis and emphysema. Repeated skin contact has been associated with bleeding into the tissue, delayed hypersensitivity and granulomas. Chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.
- **Manganese and Oxides:** Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker populations exposed to MnO including: speed and coordination of motor function are especially impaired.
- **Nickel and Oxides:** Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema, and may cause nasal or lung cancer in humans. Causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel compounds as Group 1 carcinogens (sufficient human data). ACGIH 2017 TLVs® and BEIs® lists insoluble nickel compounds as confirmed human carcinogens. Suspected of damaging the unborn child.
- **Silicon and Oxides:** Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for **Electrical Sheet** as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- **Iron Oxide:** LC₅₀: >1000 mg/L; Fish 48 h-EC₅₀ > 100 mg/L (Currenta, 2008k); 96 h-LC₀ ≥ 50,000 mg/L. Test substance: Bayferrox 130 red (95 -97% Fe₂O₃; < 4% SiO₂ and Al₂O₃) (Bayer, 1989a).
- **Aluminum Oxide:** LC₅₀ >100 mg/l for fish and algae.
- **Nickel Oxide:** IUCLID found LC50 in fish, invertebrates and algae > 100 mg/l.

12(b) Persistence & Degradability: No Data Available

12(c) Bioaccumulative Potential: No Data Available

12(d) Mobility (in soil): No data available for this product as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other Adverse Effects: None Known

Additional Information:

Hazard Category: Not Reported

Signal Word: No Signal Word

Hazard Symbol: No Symbol

Hazard Statement: No Statement

Section 13 - Disposal Considerations

Disposal: **Electrical Sheet** should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled, or classified by a competent environmental professional and disposed of in accordance with applicable federal, provincial, state or local regulations.

Container Cleaning and Disposal: Follow applicable federal, provincial, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC): 16-01-17 (ferrous metals), 12-01-99 (wastes not otherwise specified), 16-03 (off specification batches and unused products), or 15-01-04 (metallic packaging).

Please note this information is for Electrical Sheet in its original form. Any alterations can void this information.

Section 14 - Transport Information

14 (a-g) Transportation Information:

TDG / US Department of Transportation (DOT) under federal TDG and 49 CFR 172.101 **does not** regulate **Electrical Sheet** as a hazardous material. All federal, provincial, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

| | | |
|--|---|--|
| Shipping Name: Not Applicable (NA) Shipping Symbols: NA Hazard Class: NA UN No.: NA Packing Group: NA DOT/ IMO Label: NA Special Provisions (172.102): NA | Packaging Authorizations a) Exceptions: NA b) Non-bulk: NA c) Bulk: NA | Quantity Limitations a) Passenger, Aircraft, or Railcar: NA b) Cargo Aircraft Only: NA Vessel Stowage Requirements a) Vessel Stowage: NA b) Other: NA DOT Reportable Quantities: NA |
|--|---|--|

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate **Electrical Sheet** as a hazardous material.

| | | |
|--|--|---|
| Shipping Name: Not Applicable (NA) Classification Code: NA UN No.: NA Packing Group: NA ADR Label: NA Special Provisions: NA Limited Quantities: NA | Packaging a) Packing Instructions: NA b) Special Packing Provisions: NA c) Mixed Packing Provisions: NA | Portable Tanks & Bulk Containers a) Instructions: NA b) Special Provisions: NA |
|--|--|---|

International Air Transport Association (IATA) does not regulate **Electrical Sheet** as a hazardous material.

| | | | | |
|---|---|---|---|--|
| Shipping Name: Not Applicable (NA) Class/Division: NA Hazard Label (s): NA UN No.: NA Packing Group: NA Excepted Quantities (EQ): NA | Passenger & Cargo Aircraft Limited Quantity (EQ) | | Cargo Aircraft Only Pkg Inst: NA Max Net Qty/Pkg: NA | Special Provisions: NA ERG Code: NA |
| | Pkg Inst: NA Max Net Qty/Pkg: NA | Pkg Inst: NA Max Net Qty/Pkg: NA | | |

Pkg Inst – Packing Instructions Max Net Qty/Pkg – Maximum Net Quantity per Package ERG – Emergency Response Drill Code

Transport Dangerous Goods (TDG) Classification: **Electrical Sheet** does not have a TDG classification.

Section 15 - Regulatory Information

Regulatory Information: *The following listing of regulations relating to a Stelco product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.* This product and/or its constituents are subject to the following regulations:

SARA Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard.

Section 313 Supplier Notification: The product, **Electrical Sheet** contains the following toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

| CAS # | Chemical Name | Percent by Weight |
|-----------|---------------|-------------------|
| 7439-96-5 | Manganese | 2.0 max |
| 7440-02-0 | Nickel | 0.2 max |

State Regulations: The product, **Electrical Sheet** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:
 California Prop. 65: Contains elements known to the State of California to cause cancer or reproductive toxicity. This includes nickel.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Section 16 - Other Information

Prepared By: Stelco Inc.

Revision History:

- 6/30/2017 – Update to Stelco
- 5/01/2017 – Update WHMIS 2015
- 4/01/2014 - Update to OSHA HAZ COM 2012
- 12/16/10 – Update of content and format to comply with GHS
- 8/01/1985 - Original Issue

Section 16 - Other Information (continued)

Additional Information:

Hazardous Material Identification System (HMIS) Classification


| | |
|------------------------|---|
| Health Hazard | 1 |
| Fire Hazard | 0 |
| Physical Hazard | 0 |

HEALTH= 1, * Denotes possible chronic hazard if airborne dusts or fumes are generated
Irritation or minor reversible injury possible.

FIRE= 0, Materials that will not burn.

PHYSICAL HAZARDS = 0, Materials that are normally stable, even under fire conditions, will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.

FIRE = 0, Materials that will not burn.

INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not and reactive with water.

ABBREVIATIONS/ACRONYMS:

| | | | |
|-------------------------|---|--------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NIF | No Information Found |
| BEIs | Biological Exposure Indices | NIOSH | National Institute for Occupational Safety and Health |
| CAS | Chemical Abstracts Service | NTP | National Toxicology Program |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | ORC | Organization Resources Counselors |
| CFR | Code of Federal Regulations | OSHA | Occupational Safety and Health Administration |
| CNS | Central Nervous System | PEL | Permissible Exposure Limit |
| GI, GIT | Gastro-Intestinal, Gastro-Intestinal Tract | PNOR | Particulate Not Otherwise Regulated |
| HMIS | Hazardous Materials Identification System | PNOC | Particulate Not Otherwise Classified |
| IARC | International Agency for Research on Cancer | PPE | Personal Protective Equipment |
| LC50 | Median Lethal Concentration | ppm | parts per million |
| LD50 | Median Lethal Dose | RCRA | Resource Conservation and Recovery Act |
| LD_{Lo} | Lowest Dose to have killed animals or humans | RTECS | Registry of Toxic Effects of Chemical Substances |
| LEL | Lower Explosive Limit | SARA | Superfund Amendment and Reauthorization Act |
| µg/m³ | microgram per cubic meter of air | SCBA | Self-contained Breathing Apparatus |
| mg/m³ | milligram per cubic meter of air | STEL | Short-term Exposure Limit |
| mppcf | million particles per cubic foot | TLV | Threshold Limit Value |
| SDS | Safety Data Sheet | TWA | Time-weighted Average |
| MSHA | Mine Safety and Health Administration | UEL | Upper Explosive Limit |
| MOL | Ontario Ministry of Labour | WHMIS | Workplace Hazardous Materials Information System |
| NFPA | National Fire Protection Association | | |

Disclaimer: This information is taken from sources or based upon data believed to be reliable. However, Stelco Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.



The Steel Company of Canada

Electrical Sheet

Signal Word: DANGER

Symbols:



HAZARD STATEMENTS:

Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to lungs through prolonged or repeated inhalation exposure.
Harmful if swallowed.
May cause an allergic skin reaction.
May cause respiratory irritation.
Causes eye irritation.

PRECAUTIONARY STATEMENTS

Do not breathe dusts / fume.
Wear protective gloves / protective clothing / eye protection / face protection.
Contaminated work clothing must not be allowed out of the workplace.
Use only outdoors or in well ventilated areas.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not eat, drink or smoke when using this product.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If exposed, concerned or feel unwell: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Dispose of contents in accordance with federal, provincial, state and local regulations.

Stelco Inc.
386 Wilcox Street
Hamilton, ON L8L 8K5
Original Issue Date: 08/01/1985

Phone Number : (905) 528-2511 (8:00 am to 5:00 pm)
Emergency Contact: 1-888-226-8832 (CANUTEC)
Revised: 4/8/2021